## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

REF 915004
Product name VISOCOLOR HE Chloride CL 500

REACH Registration number(s): see SECTION 3.1/3.2 or
A registration number for the substance(s) does not exist because the annual tonnage does not require registration or the substance or its use is excluded from registration.

1 x 10 mL Ind. CL 500
1 x 30 mL Nitric acid 4%
1 x 100 mL TL CL 500

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**
Product for analytical use.
Exposure Scenario Classification according REACh, RIP 3.2 Codes: SU 0-2, PC 21, PROC 15, AC 0
The exposure scenario is integrated into sections 1-16.
**Uses advised against**
not described

### 1.3 Details of the supplier of the safety data sheet

**Manufactured by:**
MACHEREY-NAGEL GmbH & Co. KG
Valencienner Str. 11, 52355 Düren, GERMANY
Tel.: +49 2421 969 0 E-mail: sds@mn-net.com (msds@mn-net.com)

### 1.4 Emergency telephone number

Outside Germany (DE): Call your regional Poisons Information Service or call local Life Saving Service.
DE: Gemeinsames Giftinformationszentrum (GGIZ) 99089 Erfurt tel. +49 361 730 730

You find our current versions of SDS (22 languages) in Internet: **http://www.mn-net.com/SDS**

## SECTION 2: Hazard identification

### 2.0 Classification of the complete product



GHS02 GHS05 GHS07 GHS08

Signal word DANGER

| Hazard identification | Hazard classes/categories |
|---|---|
| H225 | Flam. Liq. 2 |
| H290 | Met. Corr. 1 |
| H302 | Acute Tox. 4 oral |
| H312 | Acute Tox. 4 derm. |
| H315 | Skin Irrit. 2 |
| H318 | Eye Dam. 1 |
| H332 | Acute Tox. 4 inh. |
| H373 | STOT RE 2 |
| H413 | Aquatic Chronic 4 |

### 2.1 Classification of the substance or mixture

**10 mL Ind. CL 500**



GHS02

Signal word DANGER

| Hazard identification | Hazard classes/categories |
|---|---|
| H225 | Flam. Liq. 2 |

**30 mL Nitric acid 4%**



GHS05 GHS07

Signal word DANGER

| Hazard identification | Hazard classes/categories |
|---|---|
| H290 | Met. Corr. 1 |
| H315 | Skin Irrit. 2 |
| H318 | Eye Dam. 1 |

**100 mL TL CL 500**



GHS07 GHS08

Signal word WARNING

| Hazard identification | Hazard classes/categories |
|---|---|
| H302 | Acute Tox. 4 oral |
| H312 | Acute Tox. 4 derm. |
| H332 | Acute Tox. 4 inh. |
| H373 | STOT RE 2 |
| H413 | Aquatic Chronic 4 |

### 2.2 Label elements

According **CLP directive** inner packages must be only labelled with GHS symbol(s) and product identificator(s) (EU 1272/2008 Annex I - 1.5.1.2).

Harmful chemicals/mixtures with signal word: **WARNING** and highly flammable chemicals/mixtures must not be labelled with H and P phrases **until 125 mL** (EU 1272/2008 Annex I - 1.5.2).
Metal corrosive solutions**do not have to** be labelled with GHS symbol, signal word, H and P phrases **until 125 mL** (EU 1272/2008 Annex I - 1.5.2.1.3).

**10 mL Ind. CL 500**



GHS02

Signal word: DANGER



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany

DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

### 30 mL Nitric acid 4%



GHS05 GHS07

Signal word: DANGER

H318
Causes serious eye damage.

P280sh, P305+351+338, P310
Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

### 100 mL TL CL 500



GHS07 GHS08

Signal word: WARNING

H413
May cause long lasting harmful effects to aquatic life.

## 2.3 Other hazards

**Possible hazards from physicochemical properties**
Generally in the case of pH values are less than 2 or higher than 11.5 then it is corrosive. In the case of pH values are less than 5 or higher than 9 then it is irritant. Flammable properties. ---

**Information pertaining to particular risks to human and possible symptoms**
Causes varying degrees of acid burns on the skin, to the eyes and to the mucous membranes and wounds which do not heal quickly depending on the concentration, temperature and the exposure time. Vapours especially which steam from hot liquids and mist can have a severe irritant effect upon the eyes and the respiratory organs.
Cause after oral intake, inhalation of vapours/dust, impairments of health when ingested in small quantities. Can accumulate within the body.
-

**Information pertaining to particular risks to the environment**
May cause long lasting harmful effects to aquatic life. Avoid contact of substance/mixture to environment.
**PBT:** not applicable
**vPvB:** not applicable

**Other hazards**
---

# SECTION 3: Composition/information on ingredients

## 3.1 Substances or 3.2 Mixtures

**10 mL Ind. CL 500**

| | | | |
|---|---|---|---|
| Chemical: | *1,5-diphenylcarbazone (metal indicator)* | | CAS No.: 538-62-5 |
| Classification: | H315, Skin Irrit. 2, H319, Eye Irrit. 2 | | |
| Formula: | $C_{13}H_{12}N_4O$ | | |
| Pseudonym: | 2-phenyl-, 2-phenylhydrazide diazenecarboxylic acid | | |
| TSCA Inventory: | listed | | |
| RTECS: | LQ9420000 | MFCD: | 00003024 |
| Concentration: | 0.1 - <1 % | | |
| acc. CLP (GHS): | The criteria for classification are not fulfilled. | | |



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

Chemical: *ethanol* CAS No.: 64-17-5
(denatured with 1%IPA/1%MEK, acc.2016/1867/EU)
Classification: H225, Flam. Liq. 2
Formula: $C_2H_6O$; $C_2H_5OH$
Pseudonym: ethyl alcohol, methylated spirit
TSCA Inventory: listed
REACH Reg. No.: 01-2119457610-43-xxxx
EC No.: 200-578-6 Indice No.: 603-002-00-5
RTECS: KQ6300000 MFCD: 00003568
KE No.: KE-13217
Concentration: 75 - <90 %
acc. CLP (GHS): H225, Flam. Liq. 2

**30 mL Nitric acid 4%**

Chemical: *nitric acid* CAS No.: 7697-37-2
Classification: H272, Ox. Liq. 2, H290, Met. Corr. 1, H314, Skin Corr. 1B, H331, Acute Tox. 3 inh.
Formula: $HNO_3 \cdot H_2O$
Pseudonym: Aqua fortis, Engravers acid, hydrogen nitrate
TSCA Inventory: listed
REACH Reg. No.: 01-2119487297-23-xxxx
EC No.: 231-714-2 Indice No.: 007-004-00-1
RTECS: QU5900000/QU5775000
KE No.: KE-25911, >10% Toxic 97-1-246, Acc. Precaution Chem.
Concentration: 3 - <5 %
acc. CLP (GHS): H290, Met. Corr. 1, H315, Skin Irrit. 2, H318, Eye Dam. 1

**100 mL TL CL 500**

Chemical: *mercury(II) nitrate* CAS No.: 7783-34-8
Classification: H302, Acute Tox. 4 oral, H312, Acute Tox. 4 derm., H332, Acute Tox. 4 inh., H373, STOT RE 2, H400, Aquatic Acute 1, H410, Aquatic Chronic 1
Formula: $Hg(NO_3)_2$
TSCA Inventory: listed
EC No.: 233-886-4 Indice No.: 080-004-00-7
KE No.: Toxic 97-1-140
Concentration: 0.86 - <3.42 % Correlation factor: x 0.58 (= %Hg)
The classification refers to weight percent of the metal (according to CLP Regulation 2008/1272/EC Annex VI, 1.1.3.2 Note 1)
acc. CLP (GHS): H302, Acute Tox. 4 oral, H312, Acute Tox. 4 derm., H332, Acute Tox. 4 inh., H373, STOT RE 2, H413, Aquatic Chronic 4

### 3.3 Remarks

When not listed, mixtures are added with water [CAS No. 7732-18-5] to 100%.

List of H and P phrases: see section 16.1

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Place insured person out of danger zone to fresh air immediately. Ensure quiet, warmth, and provide resuscitation if necessary. If necessary contact medical advice. Remove contaminated clothing. Show product package, packing insert and this material safety data sheet to the doctor.

**4.1.1 After SKIN Contact**
Remove contaminated clothing. Rinse the affected skin or mucous membrane thoroughly under running water. (If possible) use soap.

**4.1.2 After EYE Contact**
After contact with the eyes rinse thoroughly under running water with the eyelid wide open for min. 10 minutes with eye washing bottle, eye douche or running water (protect intact eye). Before (if possible) apply eye drops Proxymetacaine 0.5%, if the opening the eyelid convulsion is painful. Further treatment to be carried out by an eye specialist.

**4.1.3 After INHALATION of vapours**
After inhalation of foam or vapour fresh air should be inhaled. Keep airways free. ---

**4.1.4 After ORAL Intake**
After oral intake lots of water should be drunk after it has been ingested. ---



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

### 4.2 Most important symptoms and effects, both acute and delayed

Can accumulate within the body. ---

### 4.3 Indication of any immediate medical attention and special treatment needed

After EYE CONTACT rinse immediately with plenty of water for a long time. Eyelid convulsion measures. Name the corrosive chemical. Further treatment must to be carried out by an eye specialist. ---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Fire extinguishers appropriate to the fire classification, and, if applicable, a fire blanket must be available in a prominent location in the work area. All extinguishers like FOAM, WATER SPRAY, DRY POWDER, CARBON DIOXIDE can be used.

### 5.2 Special hazards arising from the substance or mixture

DANGER: Highly flammable (GHS regulation). Forms explosive vapour-air mixtures. Formation of hazardous and caustic vapour-air mixtures possible. ---

### 5.3 Advice for firefighters

No, for listed product. Product package burns like paper or plastic.

### 5.4 Additional information

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe vapours. Wear eye protection, respectively face protection. Regular staff training is necessary, indicating hazards and precautions on the basis of operating instructions. Restrictions on activity must be observed.

### 6.2 Environmental precautions

not necessary

### 6.3 Methods and material for containment and cleaning up

Bind any escaping liquid with inert absorbent. And dispose in accordance to local regulations for the disposal of hazardous chemicals.
Clean any contaminated equipment and floors with plenty of water.
Collect small amounts of leaked liquid and flush with water into drains.

### 6.4 Reference to other sections

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Handling in accordance with the test instruction, that comes with the product.

### 7.2 Conditions for safe storage, including any incompatibilities

The original product package of MACHEREY-NAGEL allows a safe storage.
Storage class (VCI): 3
Water hazard class (DE): 3

#### 7.2.1 Requirements for stock rooms and containers

Keep original product packages tightly closed during handling and storage. Use inbreakable container for transport of glass bottles.

### 7.3 Specific end use(s)

Product for analytical use.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

**10 mL Ind. CL 500**

Chemical: *1,5-diphenylcarbazone (metal indicator)* CAS No.: 538-62-5

Chemical: *ethanol* CAS No.: 64-17-5
DNEL: [derm] 343 mg/kg; [inh] 950 mg/m³
DNEL = Derived No-Effect Level (for workers)
$PNEC_{(fresh\ water)}$: 0.96 mg/Lno hazard identified
PNEC = Predicted No Effected Concentration



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

TRGS 900 (DE): 200 mL/m³ / 380 mg/m³
E/e respirable

Short-term exposure factor: 4 (II), Y
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 500 ppm / 960 mg/m³
NIOSH: [TWA] 1000 ppm / 1900 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 1000 ppm / 1900 mg/m³

**30 mL Nitric acid 4%**
Chemical: *nitric acid* CAS No.: 7697-37-2
DNEL: [inh] (1.3) mg/m³
DNEL = Derived No-Effect Level (for workers)

$PNEC_{(fresh\ water)}$: no hazard identified
PNEC = Predicted No Effected Concentration

EU value: 1 ppm / 2.6 mg/m³
TRGS 900 (DE): 1 ppm / 2,6 mg/m³
E/e respirable

Short-term exposure factor: -
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: 2 ppm / 5 mg/m³
NIOSH: [TWA] 2 ppm / 5 mg/m³
NIOSH STEL: 4 ppm / 10 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: List of highly hazardous chemicals, toxics and reactives Yes (TQ = 500 lbs) n/a; [TWA] 2 ppm / 5 mg/m³

**100 mL TL CL 500**
Chemical: *mercury(II) nitrate* CAS No.: 7783-34-8
EU value: [Hg] 0.02 e mg/m³
TRGS 900 (DE): [Hg] 0,02 E mg/m³
E/e respirable

Short-term exposure factor: 8 (II), H, Sh
skin resorptive (H), respiratory sensitizable (Sa), skin sensitizable (Sh), teratogenic (Z) not securely excluded / (Y) certainly excluded

SUVA(CH) MAK value: [Hg][MAK] 0,02 e/[STEL] 0,16 e mg/m³
SUVA(CH) BAT value: [Krea U/d] 35 µg/L
TRGS 903 (DE): $[U/a_{Kreatinin}]$ 25 µg/g
B blood, U urine, a no limitation, b end of exposition or shift

NIOSH: (Hg Vapor, $TWA_{skin}$) 0.05; other 0.1 mg/m³
[TWA] Time-weighted average to a reference period of 8 hours, [STEL] Short-term exposure limit related to a 15-minute period

OSHA: [TWA] 0.1 mg/m³

## 8.2 Exposure controls

Good ventilation and extraction system in the room, floor resistant to chemicals with floor drainage and washing facilities. The highest level of cleanliness must be maintained at the workplace.

**8.2.1 Respiratory protection**
No additional recommendations.

**8.2.2 Hand protection**
Yes, gloves according EN 374 (permeation time >30 min - level 2), consist of PVC, natural latex, Neopren, or Nitril (f.ex. from Ansell or KCL). Use for short times chemical resistant latex gloves with code EN 374-3 level 1.

**8.2.3 Eye protection**
Yes, safety glasses according EN 166 with integrated side shields or wrap-around protection or face protection.

**8.2.4 Skin protection**
Recommended to avoid contamination with these hazards.

**8.2.5 Personal hygiene**
Eating, drinking, smoking, taking snuff and storage of food in work areas and at outdoor workplaces is prohibited. Avoid contact with the skin, eyes and clothing. Rinse any clothing on which the substance has been spilled, and soak it in water. Wash hands thoroughly with soap and water when stopping work and before eating, and then apply protective skin cream.



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**10 mL Ind. CL 500**

| | | |
|---|---|---|
| Appearance: liquid | Colour: red | Odor: alcoholic |
| Flash point: | 20 °C | |

**30 mL Nitric acid 4%**

| | | |
|---|---|---|
| Appearance: liquid | Colour: colourless | Odor: odorless |
| pH: | 0-1 | |
| Specific gravity: | 1,03 g/cm³ | |
| Solubility in water: | 0-100 % | |

**100 mL TL CL 500**

| | | |
|---|---|---|
| Appearance: liquid | Colour: colourless | Odor: odorless |
| pH: | 1-2 | |
| Solubility in water: | 0-100 % | |

### 9.2 Other information

Data for the other parameters of the mixtures are not available, because no registration and no chemical safety report is required.
**Relevant Properties of Substance Group**
Substances are very volantile and form flammable vapour-air mixtures. ---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

no further data available.

### 10.2 Chemical stability

No known instability.

### 10.3 Possibility of hazardous reactions

No further data available.

### 10.4 Conditions to avoid

Not necessary. ---

### 10.5 Incompatible materials

Avoid contact with strong acids or alkalines.

### 10.6 Hazardous decomposition products

In the original package all parts/all reagents are safety and separated stored. Decompositions are not observed during the expiration period under recommended conditions.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

**Following information is valid for pure substances.** Quantitative data on the toxicity of this product are not available.

**10 mL Ind. CL 500**

Chemical: *1,5-diphenylcarbazone (metal indicator)* CAS No.: 538-62-5
TSCA Inventory: listed

Chemical: *ethanol* CAS No.: 64-17-5
TSCA Inventory: listed California Proposition 65 List: not listed
ACGIH: 1000 ppm
Exposure Routes: inhalation, ingestion, skin and/or eye contact
Target Organs: Eyes, skin, respiratory system, central nervous system, liver, blood, reproductive system
Symptoms: irritation eyes, skin, nose; headache, drowsiness, lassitude (weakness, exhaustion), narcosis; cough; liver damage; anemia; reproductive, teratogenic
Australia NICNAS: not listed Canada CEPA 1999: DSL yes
Japan CSCL/PRTR: not listed, Japan PDSCL: not listed
Japan ISHL: listed ≥0,1%/≥0,1%, Article 57-2 (SDS required)
South Korea TCCA: not listed
Korea Exist.Chem.Inventory: KE-13217



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

$LD50_{orl\ rat}$ : 6200 mg/kg
$LC_Low_{ihl\ gpg}$ : 21.9 g/m³
$LC_Low_{orl\ hmn}$ : 1400 mg/kg
$LC50_{ihl\ mouse}$ : [4h] 39 g/m³
$LC50_{ihl\ rat}$ : [10h] 20 g/m³
$LD50_{drm\ rbt}$ : 20 000 mg/kg
$LD50_{oral\ mouse}$ : 3450 mg/kg

TRGS 905 (DE): K5, M5, $R_F$ C

### 30 mL Nitric acid 4%

Chemical: *nitric acid* CAS No.: 7697-37-2
TSCA Inventory: listed California Proposition 65 List: not listed
Exposure Routes: inhalation, ingestion, skin and/or eye contact
Target Organs: Eyes, skin, respiratory system, teeth
Symptoms: irritation eyes, skin, mucous membrane; delayed pulmonary edema, pneumonitis, bronchitis; dental erosion
Australia NICNAS: not listed Canada CEPA 1999: DSL Yes
Japan CSCL/PRTR: not listed, Japan PDSCL: Deleterious Substance
Japan ISHL: listed ≥1,0%/≥1,0%, Article 57-2 (SDS required)
South Korea TCCA: Accident Precaution Chemical Yes
Korea Exist.Chem.Inventory: KE-25911, >10% Toxic 97-1-246, Acc. Precaution Chem.
$LC_Low_{orl\ hmn}$ : [NOAEC] 1500 mg/kg
$LC50_{ihl\ rat}$ : [4h] 2.65 mg/L

TRGS 905 (DE): $R_F$ D

### 100 mL TL CL 500

Chemical: *mercury(II) nitrate* CAS No.: 7783-34-8
TSCA Inventory: listed California Proposition 65 List: listed developmental
Exposure Routes: inhalation, skin absorption, ingestion, skin and/or eye contact
Target Organs: Eyes, skin, respiratory system, central nervous system, kidneys
Symptoms: irritation eyes, skin; cough, chest pain, dyspnea (breathing difficulty), bronchitis, pneumonitis; tremor, insomnia, irritability, indecision, headac
Japan CSCL/PRTR: PRTR: ≥1,0%Hg class I, Japan PDSCL: Poisonous substance
Japan ISHL: listed ≥0,3%/≥0,1%
Korea Exist.Chem.Inventory: Toxic 97-1-140
$LD50_{orl\ rat}$ : 26 mg/kg
$LD50_{drm\ rat}$ : 75 mg/kg
Acute Effects: Cause after oral intake, inhalation of vapours/dust, skin contact, impairments of health when ingested in small quantities.
Chronic Effects: May cause damage to organs through prolonged or repeated exposure.
TRGS 907 (DE): Sh

## SECTION 12: Ecological information

### 12.1 Toxicity

**Following information is valid for pure substances.**

**10 mL Ind. CL 500**

Chemical: *1,5-diphenylcarbazone (metal indicator)* CAS No.: 538-62-5
Water hazard class (DE): 0

Chemical: *ethanol* CAS No.: 64-17-5
$PNEC_{(fresh\ water)}$ : 0.96 mg/Lno hazard identified
PNEC = Predicted No Effected Concentration
$LC50_{daphnia\ magna/48h}$ : >100 mg/L
$LC50_{pimephales\ promelas/96h}$ : 13400 - 15100 mg/L
$LC50_{leuciscus\ idus/96h}$ : [48h] 8140 mg/L
$LC50_{fish/96h}$ : 13 g/L
$EC50_{daphnia/48h}$ : 9.3-14.2 g/L
$IC50_{scenedesmus\ quadricauda/72h}$ : [7d] 5000 mg/L
$EC10_{pseudomonas\ putita/16h}$ : [EC5] 6500 mg/L
Water hazard class (DE): 1 WGK No.: 0096
Dispersion coefficient$_{(octanol-water)}$ : -0.31



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

Storage class (VCI): 3

**30 mL Nitric acid 4%**

Chemical: *nitric acid* CAS No.: 7697-37-2
$PNEC_{(fresh\ water)}$ : no hazard identified
PNEC = Predicted No Effected Concentration
$LC50_{daphnia\ magna/48h}$ : 180 mg/L
$LC50_{fish/96h}$ : [4d] 12 g/L
Water hazard class (DE): 1 WGK No.: 0414
Storage class (VCI): 8 B

**100 mL TL CL 500**

Chemical: *mercury(II) nitrate* CAS No.: 7783-34-8
May cause long lasting harmful effects to aquatic life. Avoid contact of substance/mixture to environment.
Environmental hazards must not be labelled with P phrases until 125 mL (EU 1272/2008 Annex I - 1.5.2).
Bio Toxicity: $LC_{50}$ : $0.5_{HgCl2/48h}$ mg/L
$LC50_{fish/96h}$ : 0.17 mg/L
Water hazard class (DE): 3 WGK No.: 0406
Storage class (VCI): 6.1 B

### 12.2 Persistence and degradability

not necessary

### 12.3 Bioaccumulative potential

not necessary

### 12.4 Mobility in soil

not necessary

### 12.5 Results of PBT and vPvB assessment

no data available

### 12.6 Other adverse effects

no additional data available

## SECTION 13: Disposal considerations

Please observe local regulations for collection and disposal of hazardous waste and contact waste disposal company, where you will obtain information on laboratory waste disposal (waste code number 16 05 06).

### 13.1 Waste treatment methods

Normally it is possible to empty small amounts (diluted!) into drains. **Not for** mercury containing test solutions, please collect for disposal of hazardous waste. Empty containers of corrosive reagents prior to disposal, rinse with water.

## SECTION 14: Transport information

**14.1. UN number: 3316 14.2. UN proper shipping name: Chemical Kit**
**14.3. Class: 9 14.4. Packing group: II**
*Road transport*
Classification code: M11 Tunnel restriction code: E
Limited Quantity: acc. ADR 3.3.1/251: see LQ in Alternative declaration for transportation
*Air transport*
PAX: 960 max. weight PAX: 10 KG
CAO: 960 max. weight CAO: 10 KG
*Maritime transport*
EmS: F-A, S-P Storage category: A

Or use **Alternative declaration for transportation:**

**14.1 UN number: 2810 14.2 UN proper shipping name: Toxic liquid, organic, n.o.s. (mercury(II) nitrate solution)**
**14.3 Class: 6.1 14.4 Packing group: III**
*Road transport*
Classification code: T1
Limited Quantity: 5 L Tunnel restriction code: E
Excepted Quantity: E 1
*Air transport*
PAX: 655 max. weight PAX: 60 L



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

| | | | |
|---|---|---|---|
| CAO: | 663 | max. weight CAO: | 220 L |
| *Maritime transport* | | | |
| EmS: | F-A, S-A | Storage category: | A |

### 14.5 Environmental hazards

none, contains only small quantities of hazardous substances

### 14.6 Special precautions for user

not necessary

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

German act governing protection from hazardous substances (Chemicals Act / Chemikaliengesetz- ChemG), revised on August 2013
German order governing protection from hazardous substances (Ordinance on Hazardous Substances / Gefahrstoffverordnung - GefStoffV), revised on November 2010, according to Directive 98/24/EC
TRGS 200, German engineering rules governing the classification and labelling of hazardous substances, preparations and products, updated October 2011
MN Leaflet/User manual, also see www.mn-net.com
Look for your country-specific regulations.

### 15.2 Chemical safety assessment

**not necessary for these small amounts** ---

## SECTION 16: Other information

### 16.1 List of H and P phrases

**16.1.1 List of relevant H phrases**

| | |
|---|---|
| H225 | Highly flammable liquid and vapour. |
| H290 | May be corrosive to metals. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H332 | Harmful if inhaled. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H413 | May cause long lasting harmful effects to aquatic life. |

**16.1.2 List of relevant P phrases**

| | |
|---|---|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P260sh | Do not breathe dust/vapours. |
| P261sh | Avoid breathing dust/vapours. |
| P264W | Wash with water thoroughly after handling. |
| P273 | Avoid release to the environment. |
| P280sh | Wear protective gloves/eye protection. |
| P301+312 | IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. |
| P302+352 | IF ON SKIN: Wash with plenty of water. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P330 | Rinse mouth. |
| P390 | Absorb spillage to prevent material damage. |

### 16.2 Training advice

Multiple safety training of staffs about danger and protection by using hazards in working area. Additionally training and introduction of staffs for using these products.

### 16.3 Recommended restriction on use

Only for professional user.
Look about employee restrictions for young people (f. ex. 94/33/EC or DE § 22 JArbSchG)!
Look about employee restrictions for pregnant women and nursing women (f.ex. 92/85/EEC or for DE §§ 11-13 MuSchG 2017)!
An individual package of this product or test kit has a moderate hazardous potential.



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany

DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com

### 16.4 Further information

MACHEREY-NAGEL GmbH & Co. KG provides the information contained herein in good faith being up-to-date of own realizations at revision time. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.
MACHEREY-NAGEL GmbH & Co. KG makes NO REPRESENTATIONS or WARRANTIES, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly MACHEREY-NAGEL GmbH & Co. KG will not be responsible for damages resulting from use of or reliance upon this information. See terms and conditions at the end of our price lists for additional information.

### 16.5 Sources of key data

Regulation 453/2010/EU REACH - REQUIREMENTS FOR THE COMPILATION OF SAFETY DATA SHEETS
Regulation 487/2013/EU, 4th adaptation of CLP regulation to technical and scientific progress
Regulation 669/2018/EU, 4th adaptation of CLP regulation to technical and scientific progress
Regulation 1480/2018/EU, 4th adaptation of CLP regulation to technical and scientific progress
Regulation 849/2021/EU, 4th adaptation of CLP regulation to technical and scientific progress
TRGS 900, German engineering rules governing limits in air at work, updated 03/2019
SUVA .CH, Limits in air at work 2009, revised on 01.2009
KÜHN, BIRETT Merkblätter Gefährliche Arbeitsstoffe (Data Sheets of Hazardous Substances)

**Revisions/Updates**
*Reason for Revision: 2016-03 Adaptation of regulation 1221/2015/EU*
*2017-08 Adaption of new ethanol denaturation 2016/1867/EU*



MACHEREY-NAGEL GmbH & Co. KG · Neumann-Neander-Str. 6–8 · 52355 Düren · Germany
DE / international: Tel.: +49 24 21 969-0 Fax: +49 24 21 969-199 E-mail: info@mn-net.com
CH: Tel.: +41 62 388 55 00 Fax: +41 62 388 55 05 E-mail: sales-ch@mn-net.com
FR: Tel.: +33 388 68 22 68 Fax: +33 388 51 76 88 E-mail: sales-fr@mn-net.com
US: Tel.: +1 484 821 0984 Fax: +1 484 821 1272 E-mail: sales-us@mn-net.com